

GT-1USB/RS232

USB to Serial Converter

GT-1USB/RS232 (GT-1U/RS232) is a low cost converter using a USB port from the PC to add a serial (COM) port. Since it uses the USB type, installing and removing is fast and easy. While it supports maximum speed of 921.6Kbps for the serial port, the users can check the incoming / outgoing data by TX/RX LEDs.



Features

RS-232 Interface Supported

GT-1U/RS232 supports RS-232 interface.

15KV Surge Protector

GT-1U/RS232 has built-in 15KV Surge Protector to prevent your system from electrical shock.

9-pin D-sub male connector with TX/RX LEDs

The standard 9-pin D-sub male connector allows connection with peripheral devices easily. Real time TxD/RxD data checking is possible by the LEDs on the unit.

● GT-1USB/RS232 Specifications

Communication



Speed	Max. 921.6 Kbps
Distance	Max. 15 m
Bus Interface	USB (Universal Serial Bus)
Serial Interface	RS-232
Connector	9-pin D-sub male connector
I/O Address	Automatically configured
IRQ Number	Automatically configured
Supported OS	Windows 98/2000 (32bit)
	Windows XP/Vista/7/8 (32/64bit)
	Windows Server 2003/2008 (32/64bit)

Hardware

Dimension	33.4 x 61.0 mm
Weight	70g
Protection	±15KV ESD Protector
Power Supply	Power supply from USB port

Remark

CD	Drivers, Utility, and User Manual
----	-----------------------------------